

FAÇADE LIGHTS SPECIFICATION SHEET



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

UL345CARGB

110° colour change wall washing light bar (12W max.)

FEATURES

IP rating	IP65
IK rating	IK02
Colour flexibility	RGB
Tilttable	180°
Input	Driver Required
LED Lifetime	50,000h L50 B50

INSTALLATION INFORMATION

Bathroom zone	1
Construction Material	Anodised aluminium
Weight	0.7kg
Maximum ambient temperature	35°C
Electric Class (1, 2, 3)	3

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

- Surface mount in multiple applications
- Full RGB colour range
- Compatible with a large range of controllers
- Anodised aluminium for use in outdoor and indoor environments
- Removable feet can be used anywhere along the base or sides. Allen key included

PHOTOMETRICS @ 25°C

Product code	Finish	Wattage	Colour	Beam angle	lm	lm/W	lx @ 1m
UL345CARGB	Black		White	110°	-	-	-
UL345CARGB	Black	4	Red	110°	96	24	32
UL345CARGB	Black	4.1	Green	110°	161	39	57
UL345CARGB	Black	4.3	Blue	110°	51	12	19

WIRING INFORMATION

Cable / Flying Lead	1x 3m LED RGB 0.75mm ² cable (outside diameter: 6mm)
Type of Wiring Required	N/A (1 per power repeater)

LED DRIVER

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PR3011	220-240V	N/A	Yes	1	1	1

ACCESSORIES

JB3	Waterproof junction box
LED RGB 0.75 CABLE	4-core PVC cable
ULBRACKET	2 piece black anodised aluminium bracket

